

40mm · 1 1/2" composite cartridge · X-type						40mm · 1 1/2" composite cartridge · C-type						40mm · 1 1/2" composite cartridge · D-type					
Pressure range, ΔP: 15-130 kPaD · 2.2-18.9 psid						Pressure range, ΔP: 22-300 kPaD · 3.2-43.5 psid						Pressure range, ΔP: 30-410 kPaD · 4.4-59.5 psid					
Model no.			ABV2.X.W	ABV2.X.R	Model no.			ABV2.C.W	ABV2.C.R	Model No.			ABV2.D.W	ABV2.D.R			
Controlled flow rate	l/sec	l/hr	GPM	White	Red	l/sec	l/hr	GPM	White	Red	l/sec	l/hr	GPM	White	Red		
	0.17	612	2.69	1		0.23	828	3.65	1		0.27	972	4.28	1			
	0.23	828	3.64	2		0.31	1120	4.91	2		0.36	1300	5.71	2			
	0.26	936	4.12		1	0.38	1370	6.02		1	0.44	1580	6.97		1		
	0.33	1190	5.23	3		0.42	1510	6.66	3		0.52	1870	8.24	3			
	0.38	1370	6.02	4		0.47	1690	7.45	4		0.58	2090	9.19	4			
	0.39	1400	6.18		2	0.50	1800	7.93		2	0.60	2160	9.51		2		
	0.48	1730	7.61	5	3	0.60	2160	9.51	5		0.74	2660	11.7	5			
	0.54	1940	8.56	6		0.64	2300	10.1		3	0.76	2740	12.0		3		
	0.62	2230	9.83	7		0.68	2450	10.8	6		0.83	2990	13.2	6			
	0.63	2270	9.99		4	0.78	2810	12.4	7		0.93	3350	14.7	7			
	0.66	2380	10.5	8		0.83	2990	13.2		4	0.99	3560	15.7	8	4		
	0.67	2410	10.6		5	0.84	3020	13.3	8		1.07	3850	17.0		5		
	0.76	2740	12.0		6	0.90	3240	14.3		5	1.28	4610	20.3		6		
	0.85	3060	13.5		7	1.07	3850	17.0		6	1.39	5000	22.0		7		
						1.17	4210	18.5		7	1.43	5150	22.7		8		
						1.21	4360	19.2		8							

Accuracy: Greatest of either ±10% of controlled flow rate or 20 l/hr (0.0056 l/sec or 0.088 GPM).