

50mm · 2" · stainless steel cartridge											
Controlled flow rate	Pressure range, ΔP:			10-95 kPaD 1-14 psid		22-210 kPaD 2-32 psid		40-390 kPaD 4-57 psid		90-880 kPaD 8-128 psid	
	l/sec	l/hr	GPM	Type 1		Type 2		Type 4		Type 8	
				Marking	FlowCon	Marking	FlowCon	Marking	FlowCon	Marking	FlowCon
	0.757	2730	12.0	36-1	F3C2136						
	0.883	3180	14.0	42-1	F3C2142						
	1.01	3630	16.0	48-1	F3C2148						
	1.14	4090	18.0	54-1	F3C2154	36-2	F3C2236				
	1.26	4540	20.0	60-1	F3C2160						
	1.32	4770	21.0			42-2	F3C2242				
	1.39	5000	22.0	66-1	F3C2166						
	1.51	5450	24.0	72-1	F3C2172	48-2	F3C2248	36-4	F3C2436		
	1.64	5910	26.0	78-1	F3C2178						
	1.70	6130	27.0			54-2	F3C2254				
	1.77	6360	28.0	84-1	F3C2184			42-4	F3C2442		
	1.89	6810	30.0	90-1	F3C2190	60-2	F3C2260				
	2.02	7270	32.0	96-1	F3C2196			48-4	F3C2448		
	2.08	7490	33.0			66-2	F3C2266				
	2.15	7720	34.0	102-1	F3C21102						
	2.27	8180	36.0	108-1	F3C21108	72-2	F3C2272	54-4	F3C2454	36-8	F3C2836
	2.40	8630	38.0	114-1	F3C21114						
	2.46	8860	39.0			78-2	F3C2278				
	2.52	9080	40.0					60-4	F3C2460		
	2.65	9540	42.0			84-2	F3C2284			42-8	F3C2842
	2.78	9990	44.0					66-4	F3C2466		
	2.84	10200	45.0			90-2	F3C2290				
	3.03	10900	48.0			96-2	F3C2296	72-4	F3C2472	48-8	F3C2848
	3.22	11600	51.0			102-2	F3C22102				
	3.28	11800	52.0					78-4	F3C2478		
	3.41	12300	54.0			108-2	F3C22108			54-8	F3C2854
	3.53	12700	56.0					84-4	F3C2484		
	3.60	12900	57.0			114-2	F3C22114				
	3.79	13600	60.0					90-4	F3C2490	60-8	F3C2860
	4.04	14500	64.0					96-4	F3C2496		
	4.16	15000	66.0							66-8	F3C2866
	4.29	15400	68.0					102-4	F3C24102		
	4.54	16400	72.0					108-4	F3C24108	72-8	F3C2872
	4.79	17300	76.0					114-4	F3C24114		
	4.92	17700	78.0							78-8	F3C2878
	5.30	19100	84.0							84-8	F3C2884
	5.68	20400	90.0							90-8	F3C2890
	6.06	21800	96.0							96-8	F3C2896
	6.44	23200	102							102-8	F3C28102
	6.81	24500	108							108-8	F3C28108
	7.19	25900	114							114-8	F3C28114

Accuracy: ±5% of controlled flow rate.